



SAFETY DATA SHEET
According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

1. IDENTIFICATION

Product identifier

Product name FLUIDMATIC MV LV

Other means of identification

Product Code(s) 084045

Number BSN
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Transmission fluid.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number +1 (908) 862-9300
Emergency telephone +1 866 928 0789 (24h/24, 7d/7)
+1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

Unknown Acute Toxicity

92.517% of the mixture consists of ingredient(s) of unknown toxicity

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	80-<90
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	1-<3
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate	125643-61-0	1-<2,5
bis(nonylphenyl)amine	36878-20-3	1-<2,5
Reaction product of alkylthioalcohol and substituted phosphorus compound	^	0,1-<1

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. Rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.

Skin contact

Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital. Wash off immediately with soap and plenty of water.

Inhalation

Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

respiratory tract.

Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately. If swallowed, do not induce vomiting - seek medical advice.

Most important symptoms/effects, acute and delayed

Skin contact

Not classified.

Eye contact

Not classified.

Inhalation

Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion

Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Dry powder. Carbon dioxide (CO₂). Water spray. ABC powder.

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

Special Hazard

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge

None.

None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information

Use personal protective equipment.
Evacuate non-essential personnel.
Ensure adequate ventilation, especially in confined areas.
ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery.

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

Other information

Remove all sources of ignition.
Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames.

Environmental precautions

General Information

Prevent further leakage or spillage if safe to do so. Dike to collect large liquid spills. The product should not be allowed to enter drains, water courses or the soil. Local authorities should be advised if significant spillages cannot be contained. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Try to prevent the material from entering drains or water courses. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion

Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

Control parameters

Exposure limits

Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Exposure controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Eye/Face Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots.

Hand Protection

Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color

red

Physical State @20°C

liquid

Odor

No information available

Odor Threshold

No information available

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point	220 °C 428 °F		
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.873	@ 15 °C	
Density	873 kg/m ³	@ 15 °C	
Water solubility		No information available	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		Not applicable	
Decomposition temperature		No information available	
Viscosity, kinematic	27.5 mm ² /s 6.0 mm ² /s	@ 40 °C @ 100 °C	ASTM D 2983 ASTM D 445
Explosive properties	No information available		
Oxidizing Properties	No information available		
Possibility of hazardous reactions	No information available		
<u>Other information</u>			
Freezing Point		No information available	

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	No information available.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Conditions to Avoid</u>	Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Heat, flames and sparks. Take precautionary measures against static discharges. Strong oxidizing agents.
<u>Incompatible Materials</u>	Strong oxidizing agents.
<u>Hazardous Decomposition Products</u>	None under normal use. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATIONInformation on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Skin contact	Not classified.
Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Oral ATEmix (oral)	5405 mg/kg
Dermal ATEmix (dermal)	5141 mg/kg
Inhalation ATEmix (inhalation-dust/mist)	5.6 mg/l
ATEmix (inhalation-vapor)	625.5 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0	LD50 > 5000 mg/kg bw (Rat - OECD TG 401)	LD50 > 2000 mg/kg (Rabbit - OECD 402)	LD50 (4h) > 5.53 mg/l (Rat - OECD 403)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	LD50 > 2000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
bis(nonylphenyl)amine 36878-20-3	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
Reaction product of alkylthioalcohol and substituted phosphorus compound ^	LD50 > 2000 mg/kg bw (rat)	LD50 > 500 mg/kg bw (rabbit)	

Sensitization Not classified as a sensitizer.
Carcinogenicity This product is not classified carcinogenic.

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7				-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0	-	-		

Mutagenicity

This product is not classified as mutagenic.

Reproductive toxicity

This product does not present any known or suspected reproductive hazards.

Aspiration Hazard

Not classified.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		LL50 (96h) > 100 mg/l (OECD TG 203)	EL50 (48h) > 10000 mg/l (OECD TG 202)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	EC50 (72h) > 3 mg/l (Scenedesmus sp. - OECD 201)	LC50 (96h) > 74 mg/l (Brachydanio rerio - semi static - OECD 203)	EC50(24h) > 100 mg/l (Daphnia magan - OECD 202)	
bis(nonylphenyl)amine 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)	LC50 (96h) > 100 mg/l (Brachydanio rerio - OECD 203)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	
Reaction product of alkylthioalcohol and substituted phosphorus compound ^	EL50 (72h) 0.31 mg/l (Pseudokirchnerella subcapitata)	CL50 (96h) 1.5 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (24h) 2 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (48h) 1.7 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (72h) 1.6 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (96h) 1.5 mg/l	EL50 (48h) 0.09 mg/l (Daphnia magna - OECD 202)	

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

		(Oncorhynchus mykiss - OECD 203)		
--	--	----------------------------------	--	--

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		NOEL (21d) = 10 mg/l (OECD TG 202)	NOELR (14d) > 1000 mg/l (QSAR modelled data)	
Reaction product of alkylthioalcohol and substituted phosphorus compound ^	NOELR (72h) 0.13 mg/l (Pseudokirchnerella subcapitata) NOELR (72h) < 0.13 mg/l (Pseudokirchnerella subcapitata)	NOEC (21d) 0.14 mg/l (Daphnia magna) LOEC (21d) 0.35 mg/l (Daphnia magna) LL50 (21d) 0.22 mg/l (Daphnia magna)		

Effects on terrestrial organisms No information available.**Persistence and degradability****General Information** No information available.**Bioaccumulative potential****Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0	6.1
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	9.2
bis(nonylphenyl)amine 36878-20-3	7.7

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility

Air Loss by evaporation is limited

Water Insoluble The product spreads on the surface of the water.

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with local regulations. Should not be released into the environment.

Contaminated packaging Dispose of in accordance with local regulations.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

Environmental hazard Yes

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	no
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	Weight %	California Prop. 65
Ethylbenzene - 100-41-4	0.00029	Carcinogen

U.S. State Right-to-Know Regulations

No information available

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 1	Flammability 1	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

Version GNAM



SDS # : 084045

FLUIDMATIC MV LV

Date of the previous version: 2016-03-15

Revision Date: 2016-07-06

Version 2.01

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2016-07-06**Revision Note** *** Indicates updated section**Abbreviations, acronyms**

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDLH - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

Version GNAM