



# PEAK

## SYNTHETIC BLEND MOTOR OIL

### DESCRIPTION:

PEAK® SYNTHETIC BLEND MOTOR OILS formulated with FMX offer superior oxidation stability, extra protection against heavy load conditions, additional high temperature protection, and better cold weather properties than conventional motor oils. This combination provides increased protection for tough driving conditions that put stress and demands on your engine.

### BENEFITS:

- Advanced synthetic blend offers better anti-oxidancy, sludge control and TBN retention
- For Everyday Use
- Exceeds protection requirements of all major OEMs where API SN oils are recommended
- Compatible with leading conventional and synthetic motor oils
- Formulated with a new ZDDP additive for extended wear performance

### APPLICATION:

PEAK® SYNTHETIC BLEND MOTOR OIL is recommended for use in all gasoline engines (including turbocharged), in passenger cars, light-duty trucks, vans and sport utility vehicles. PEAK® SYNTHETIC BLEND MOTOR OIL SAE 5W-20, 5W-30 AND 10W-30 exceed the demanding requirements of the International Lubricant Standardization and Approval Committee (ILSAC) GF-5. GF-5 is the latest standard for passenger car, van, light-duty truck and sport utility engine oils. It also exceeds API SN Service Classification requirements. Always consult your owner's manual for correct viscosity choice and API Service Classification requirements.



### SHIPPING INFORMATION:

|                         |                 |                |
|-------------------------|-----------------|----------------|
| Pack                    | 6/1 Quart       | 55 Gallon Drum |
| Unit Weight (lbs.)      | 2.1             | 450            |
| Case/Pallet Weight*     | 12.3/2108       | 1850           |
| Units per Pallet        | 1008            | 4              |
| Cases per Pallet        | 168             | -              |
| Units per Truck         | 24192           | 84             |
| Cases/Pallets per Truck | 4032/24         | 21             |
| Case Size (inches)      | 8.9 x 7.4 x 8.8 | -              |
| Cases per row/Rows high | 24/7            | -              |
| Pallet Size (inches)    | 48 x 40 x 72.3  | 46X48X40.5     |

(\* Including pallet weight of 50 lbs.)

### PRODUCT INFORMATION:

|  | 5W-20              | 5W-30              | 10W-30        |
|--|--------------------|--------------------|---------------|
| Quart Part Number                      | P2MB576            | P3MB576            |               |
| Drum Part Number                       | P2MB51             | P3MB51             |               |
| Bulk Part Number                       | P2MS50             | P3MS50             | P3MS10        |
| ILSAC                                  | GF-5               | GF-5               | GF-5          |
| API                                    | SN                 | SN                 | SN            |
| Test (Method)                          | <b>5W-20</b>       | <b>5W-30</b>       | <b>10W-30</b> |
| Specific Gravity @ 60 °F (ASTM D-4052) | 0.8614             | 0.8608             | 0.8713        |
| Viscosity                              |                    |                    |               |
| @ 40 °C, cSt (ASTM D-445)              | 49.68              | 63.05              | 66.68         |
| @ 100 °C, cSt (ASTM D-445)             | 8.55               | 10.6               | 10.4          |
| Viscosity Index (ASTM D-2270)          | 150                | 158                | 138           |
| Pour Point                             | -46°C              | -45°C              | -41°C         |
| Flash Point (ASTM D-92)                | 206°C              | 204°C              | 204°C         |
| Noack Volatility %                     | 14.2               | 14.3               | 12            |
|  | <b>5W-20</b>       | <b>5W-30</b>       |               |
| Quart UPC Code                         | 0-74804-05322-7    | 0-74804-05323-4    |               |
| Case UPC Code                          | 0-74804-15322-4    | 0-74804-15323-1    |               |
| Case SCC-14 Code                       | 1-00-74804-05322-4 | 1-00-74804-05323-1 |               |
| 55 Gallon Drum UPC Code                | 0-74804-05354-8    | 0-74804-05355-5    |               |



OFFICIAL MOTOR OIL OF  
michael waltrip racing

# PEAK MOTOR OIL



## PERFORMANCE WITHOUT COMPROMISE

At PEAK, we're the independent guys, running a family owned business that's nothing like Big Oil. Here, American made quality and value go into good, honest products, with everything your engine needs to run right for the long haul.



CHECK OUT  
OUR OTHER  
TRUSTED  
PRODUCTS



Clint Bowyer



Connect with PEAK



PEAKAUTO

WWW.PEAKAUTO.COM

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at [www.peaklubricants.com](http://www.peaklubricants.com), or by calling Old World Industries' PEAK technical support line at 1-800-477-5847.

"Clint Bowyer" is a registered trademark of Clint Bowyer. His name and likeness are used under license by Clint Bowyer Racing, Inc. Stylized #15 is a pending trademark of Michael Waltrip Racing Holdings, LLC and is used under license. Michael Waltrip Racing logo, stylized #15, and the likeness of the #15 race car are trademark/pending trademarks (#15) of Michael Waltrip Racing Holdings, LLC and are used under license. TOYOTA AND ALL ASSOCIATED MARKS, EMBLEMS AND DESIGNS ARE INTELLECTUAL PROPERTY RIGHTS OF TOYOTA MOTOR CORPORATION AND USED WITH PERMISSION.



We Support  
Be Car Care Aware  
[www.carcare.org](http://www.carcare.org)

Distributed by Old World Industries, LLC Northbrook, IL 60062

800.323.5440 [www.peakauto.com](http://www.peakauto.com)

©2013 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

# RUN TRUE™