



DESCRIPTION:

PEAK® SAE 75W-90 FULL SYNTHETIC GEAR OIL is a multi-purpose full synthetic gear oil formulated to meet the latest requirements of gear manufacturers requiring API GL-5 lubricants. PEAK® SAE 75W-90 FULL SYNTHETIC GEAR OIL is a blend of high quality base stocks with extreme pressure additives that provide protection under severe operating conditions, including automotive applications.

PEAK® SAE 75W-140 FULL SYNTHETIC GEAR OIL is a full synthetic gear oil that provides exceptional protection under severe operating conditions. PEAK® SAE 75W-140 FULL SYNTHETIC GEAR OIL is a multi-purpose gear oil that exceeds the latest requirements of gear and transmission manufacturers requiring API GL-5 or API MT-1 level lubricants.

BENEFITS:

- Limited Slip
- Meets API GL-5 specification
- Meets MT-1 specification
- Meets Mack GO-J, GO-H, GO-G specification
- Meets MIL-L-2105D Military specification
- Meets ArvinMeritor (Rockwell International) 076-E
- Outstanding anti-weld, anti-scuff and anti-wear properties
- Provides exceptional gear and bearing protection
- Helps prevent wear caused by lubrication foaming and aeration
- Protects against damaging rust and corrosion

APPLICATION:

PEAK® SAE 75W-90 and 75W-140 FULL SYNTHETIC GEAR OILS are recommended for use in limited slip differentials, manual transmissions, final drives and other gear cases in passenger cars, light duty trucks as well as axles of heavy duty trucks, off-road equipment, tractors and outboard motors.

Viscosity recommendations vary according to temperature and manufacturer. Always consult your owner's manual for correct viscosity choice and service category recommendation.

SHIPPING INFORMATION:

	6/1 Quart	5 Gallon Pail	16 Gallon Keg	55 Gallon Drum	Bag in a Box
Pack	2	40.6	140	450	43
Unit Weight (lbs.)	2	40.6	140	450	43
Pallet Weight*	1,246	1,755.2	1,310	1,850	1806**
Units per Pallet	528	42	9	4	-
Cases per Pallet	88	-	-	-	42
Units per Truck	11,088	882	189	84	-
Pallets per Truck	21	21	21	21	924/22
Case Size (Inches)	-	-	-	-	19 x 13 x 7.25
Cases per row/Rows High	22/4	14/3	-	-	7/6
Pallet Size (Inches)	-	-	-	-	40 x 48

(* Including pallet weight of 50lbs.

PRODUCT INFORMATION:

Test (Method)	75W-90	75W-140	75W-90	75W-140
API Gravity (ASTM D-287)	31.67	33.73	Quart Part Number	P9GS776 P4GS776
Viscosity			Pail Part Number	P9GS75 P4GS75
@ 40 °C, cSt (ASTM D-445)	104.7	193.4	Keg Part Number	P9GS76 P4GS76
@ 100 °C, cSt (ASTM D-445)	15.9	28.4	Drum Part Number	P9GS71 P4GS71
Viscosity Index (ASTM D-2270)	162	186	Bulk Part Number	P9GF70 P4GF70
Quart UPC Code	0-74804-04294-8	0-74804-04295-5		
Quart Case UPC Code	0-74804-14294-5	0-74804-14295-2	Bag in a Box Part Number	P9GF7BX6
Quart SCC-14 Code	1-00-74804-04294-5	1-00-74804-04295-2		
Pail UPC Code	0-74804-03462-2	0-74804-03465-3		
Keg UPC Code	0-74804-03463-9	0-74804-03466-0		
Drum UPC Code	0-74804-03461-5	0-74804-03464-6		
Bag in a Box UPC Code	0-74804-06231-1	-		



Distributed by Old World Industries, LLC Northbrook, IL 60062

p 800.323.5440 www.peakauto.com

©2016 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

RUN TRUE™