



DESCRIPTION:

PEAK® FULL SYNTHETIC MOTOR OILS are formulated with high quality synthetic base stocks and are fortified with an advanced additive technology to provide maximum protection for today's modern engines.

BENEFITS:

- Meets most warranty requirements for U.S., European and Japanese cars and light trucks with gasoline and gasoline turbo charged engines where API SN, SM, SL, SJ or SH are specified
- Exceeds ILSAC GF-5 energy conserving performance standards
- Protects engines under demanding stop and go driving conditions
- Meets the highest U.S. standards for automotive engine wear protection

APPLICATION:

PEAK FULL SYNTHETIC MOTOR OILS are recommended for use in all gasoline engines, including turbocharged, in passenger cars, light-duty trucks, vans and sport utility vehicles. Always consult your owner's manual for correct viscosity choice and API Service Category recommendations. PEAK FULL SYNTHETIC MOTOR OILS are not recommended for use in diesel engines.

SHIPPING INFORMATION:

	6/1 Quart	3/5 Quart	55 Gallon Drum
Unit Weight (lbs.)	2.1	10.1	450
Case/Pallet Weight*	12.3/2108	31.2/1797	1850
Units per Pallet	1008	168	4
Cases per Pallet	168	56	-
Units per Truck	21168	4032	84
Cases/Pallets per Truck	3528/21	1344/24	21
Case Size (inches)	8.9 x 7.4 x 8.8	14.3 x 7.9 x 12.5	-
Cases per row/Rows high	24/7	14/4	-
Pallet Size (inches)	48 x 40 x 72.3	48 x 40 x 58.3	46 x 48 x 40.5

* Including pallet weight of 50 lbs.

PRODUCT INFORMATION:

	OW-20	OW-20 dexos1	5W-20 dexos1	5W-30 dexos1	10W-30
Quart Part Number	-	P2MS076	P2MS576	P3MS576	P3MS176
5 Quart Part Number	-	P2MS05	P2MS55	P3MS55	P3MS15
Drum Part Number	-	P2MS01	P2MS51	P3MS51	P3MS11
Bulk Part Number	P2MF00	P2MF000	P2MF50	P3MF50	P3MF10
API Classification	SN	SN	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5	GF-5	GF-5
Test (Method)	OW-20	OW-20 dexos1	5W-20 dexos1	5W-30 dexos1	10W-30
API Gravity (ASTM D-287)	35.62	35.62	34.76	34.35	33.86
Viscosity					
'@ 40 °C, cSt (ASTM D-445)	42.71	42.71	47.26	57.86	62.97
'@ 100 °C, cSt (ASTM D-445)	8.06	8.06	8.53	10.14	10.23
Viscosity Index (ASTM D-2270)	165	165	159	164	150
Sulfated Ash. % Mass	0.83	0.83	0.9	0.92	0.91
Pour Point	-51°C	-51°C	-48°C	-45°C	-45°C
Flash Point	224°C	224°C	228°C	226°C	228°C
Noack Volatility %	13.8	13.8	11.7	11.2	11.7
Quart UPC Code	0-74804-03474-5		0-74804-02033-5	0-74804-02031-1	0-74804-02035-9
Case UPC Code	0-74804-14070-5		0-74804-14071-2	0-74804-14072-9	0-74804-14073-6
Case SCC-14 Code	1-00-74804-04070-5		1-00-74804-04071-2	1-00-74804-04072-9	1-00-74804-04073-6
5 Quart UPC Code	0-74804-03897-2		0-74804-03898-9	0-74804-03899-6	0-74804-03900-9
Case UPC Code	0-74804-13897-9		0-74804-13898-6	0-74804-13899-3	0-74804-13900-6
Case SCC-14 Code	1-00-74804-03897-9		1-00-74804-03898-6	1-00-74804-03899-3	1-00-74804-03900-6
Drum UPC Code	0-74804-03491-2		0-74804-03442-4	0-74804-03443-1	0-74804-03492-9

OW-20, 5W-20, and 5W-30 are licensed dexos1 products



Distributed by Old World Industries, LLC Northbrook, IL 60062
 p 800.323.5440 www.peakauto.com

©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

RUN TRUE™