

TOTAL CLASSIC 5W-30



“TOTAL CLASSIC, the guaranteed quality”

Synthetic technology multigrade oil for gasoline and Diesel engines, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers (ACEA).

APPLICATIONS

All gasoline/Diesel engines
Direct injection Diesel

The most severe journeys
All times of year

“Vigorous” driving

- Developed to cover the most stringent requirements of **both recent gasoline and Diesel engines** (since MY 2000).
- Particularly suited to **turbocharged, multi-valve and direct injection engines**.
- Perfectly **adapted to all vehicles equipped with catalysts** and using unleaded fuel or liquefied petroleum gas.
- Can be used in the **most difficult operating conditions** (motorways, dense city traffic...), **whatever the season**.
- For all driving styles, particularly “vigorous” and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

ACEA A5/B5
API SL/CF

CUSTOMER BENEFITS

High performance

Lengthens engine life

Extended oil change intervals

- Excellent engine protection and oxidation resistance.
- Easy cold starts and fuel economies due to its extreme fluidity.
- Immediate lubrication of engine parts during cold starts at low engine temperature, leading to longer engine life.
- Meets the main technical requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

TOTAL CLASSIC 5W-30	Units	SAE Grade 5W-30
Volumetric mass at 15°C	kg/m ³	853
Viscosity at 40°C	mm ² /s	57
Viscosity at 100°C	mm ² /s	9.9
Viscosity index	-	160
Flash point Cleveland	°C	224
Pour point	°C	-36

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS

Le Spazio, 562 avenue du Parc de l'île
92029 Nanterre Cedex
FRANCE
1/1

TOTAL CLASSIC 5W-30
Sheet updated : 02/14



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.