



DESCRIPTION:

PEAK® HIGH MILEAGE MOTOR OIL is specifically formulated with a unique combination of premium base oils and an enhanced additive system to provide increased protection for higher mileage engines.

BENEFITS:

- Developed with advanced additives that help condition and restore seals which helps prevent oil seepage often observed on the ground beneath the vehicle
- Can help minimize oil consumption and maximize compression to restore lost power
- Contains special detergents to help clean existing sludge and deposits in high mileage engines
- Enhanced deposit control to protect vital engine parts
- Formulated to help deliver superior reduction of friction and abrasion
- Backward compatible with earlier API/ILSAC performance levels

APPLICATION:

PEAK HIGH MILEAGE MOTOR OIL is recommended for use in vehicles with more than 75,000 miles. Use to protect critical engine parts from lubricant related failures for up to 1 full year or 7,500 miles (12,100 Km), whichever comes first. Visit PEAKauto.com and see PEAK's Motor Oil Limited Warranty to learn more. Follow your vehicle's OEM recommended oil change interval if under warranty.

SHIPPING INFORMATION:

Pack	6/1 Quart	55 Gallon Drum	Bag in a Box
Unit Weight (lbs.)	2.1	450	43
Case/Pallet Weight*	12.3/2108	1850	1806**
Units per Pallet	1008	4	-
Cases per Pallet	168	-	42
Units per Truck	21168	84	-
Cases/Pallets per Truck	3528/21	21	924/22
Case Size (inches)	8.9 x 7.4 x 8.8	-	19 x 13 x 7.25
Cases per Row/Rows High	24/7	-	7/6
Pallet Size (inches)	48 x 40 x 72.3	46 x 48 x 40.5	40 x 48

(*) Including pallet weight of 50 lbs. ** Based on 42 cases per skid



PRODUCT INFORMATION:

	5W-20	5W-30	10W-30	10W-40
Quart Part Number	P2MH576	P3MH576	P3MH176	P4MH176
Drum Part Number	P2MH51	P3MH51	P3MH11	P4MH11
Bulk Part Number	P2MH50	P3MH50	P3MH10	P4MH10
Bag in a Box Part Number	-	P3MH5BX6	P3MH1BX6	-
API Classification	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ
ILSAC	GF-5, GF-4 & GF-3	GF-5, GF-4 & GF-3	GF-5, GF-4 & GF-3	-
Meets Ford	WSS-M2C945A, WSS-M2C930A & WSS-M2C153	WSS-M2C946A & WSS-M2C929A	-	-
Chrysler	MS-6395 & MS-10797	MS-6395	-	-
General Motors	6094M	6094M	6094M	-
Test (Typical)	5W-20	5W-30	10W-30	10W-40
Viscosity @ 100 °C, cSt	8.58	9.94	10.4	15.5
Viscosity Index	158	159	151	155
Noack Volatility	13.5	13.5	13.0	13.0
Quart UPC Code	0-74804-04210-8	0-74804-04211-5	0-74804-04212-2	0-74804-04213-9
Case UPC Code	0-74804-15161-9	0-74804-14801-5	0-74804-14837-4	0-74804-15164-0
Case SCC-14 Code	1-00-74804-05161-9	1-00-74804-04801-5	1-00-74804-04837-4	1-00-74804-05164-0
55 Gal Drum UPC Code	0-74804-04260-3	0-74804-04261-0	0-74804-04262-7	0-74804-04263-4
Bag in a Box UPC Code	-	0-74804-06222-9	0-74804-06223-6	-



Distributed by Old World Industries, LLC Northbrook, IL 60062

p 800.323.5440 www.peakauto.com

©2017 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

Ver 170927

RUN TRUE™