



PEAK

CONVENTIONAL MOTOR OIL

DESCRIPTION:

PEAK® MULTIGRADE MOTOR OIL is formulated with an advanced additive technology and premium base oils for high performance and longer engine life.

BENEFITS:

- Exceeds API SN Service Classification (all grades)
- Exceeds ILSAC GF-5 requirements (SAE 5W-20, 5W-30 and 10W-30)
- Meets passenger car and light-duty truck manufacturers' warranty requirements
- Meets the highest U.S. standards for automotive engine wear protection

APPLICATION:

PEAK® MULTIGRADE MOTOR OIL is recommended for use in all gasoline engines (including turbocharged), in passenger cars, light-duty trucks, vans and sport utility vehicles. PEAK® MULTIGRADE MOTOR OIL SAE 5W-20, 5W-30 AND 10W-30 exceed the demanding requirements of the International Lubricant Standardization and Approval Committee (ILSAC) GF-5. GF-5 is the latest standard for passenger car, van, light-duty truck and sport utility engine oils. It also exceeds API SN Service Classification requirements. Always consult your owner's manual for correct viscosity choice and API Service Classification requirements.

SHIPPING INFORMATION:

| | 6/1 Quart | 3/5 Quart | 55 Gallon Drum |
|-------------------------|-----------------|-------------------|----------------|
| Pack | 6/1 Quart | 3/5 Quart | 55 Gallon Drum |
| Unit Weight (lbs.) | 2.1 | 10.1 | 450 |
| Case/Pallet Weight* | 12.3/2108 | 31.2/1797 | 1850 |
| Units per Pallet | 1008 | 168 | 4 |
| Cases per Pallet | 168 | 56 | - |
| Units per Truck | 24192 | 4032 | 84 |
| Cases/Pallets per Truck | 4032/24 | 1344/24 | 21 |
| Case Size (inches) | 8.9 x 7.4 x 8.8 | 14.3 x 7.9 x 12.5 | - |
| Cases per row/Rows high | 24/7 | 14/4 | - |
| Pallet Size (inches) | 48 x 40 x 72.3 | 48 x 40 x 58.3 | 46 x 48 x 40.5 |

(* Including pallet weight of 50lbs.)

| PRODUCT INFORMATION: | 5W-20 | 5W-30 | 10W-30 | 10W-40 | 20W-50 |
|--------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Quart Part Number | P2M0576 | P3M0576 | P3M0176 | P4M0176 | P5M0276 |
| 5 Quart Part Number | P2M055 | P3M055 | P3M015 | P4M015 | P5M024 |
| Drum Part Number | P2M051 | P3M051 | P3M011 | P4M011 | P5M021 |
| Tote Part Number | P2M052 | - | - | - | - |
| Bulk Part Number | P2MS50 | P3MS50 | P3MS10 | P4M010 | P5M020 |
| API Classification | SN | SN | SN | SN | SN |
| ILSAC | GF-5 | GF-5 | GF-5 | - | - |
| Test (Method) | 5W-20 | 5W-30 | 10W-30 | 10W-40 | 20W-50 |
| API Gravity (ASTM D-287) | 32 | 32 | 31 | 31 | 27.5 |
| Flash Point °C | 202 | 206 | 202 | 202 | 204 |
| Pour Point °C | -33 | -39 | -30 | -30 | -21 |
| Viscosity | | | | | |
| '@ 40 °C, cSt (ASTM D-445) | 46 | 55 | 68 | 106 | 161 |
| '@ 100 °C, cSt (ASTM D-445) | 8.58 | 9.94 | 10.4 | 15.5 | 18.2 |
| Viscosity Index (ASTM D-2270) | 165 | 169 | 139 | 155 | 126 |
| Noack Volatility (ASTM D-5800) | 12.6 | 14.5 | 15.2 | 14.9 | 6.2 |
| Sulfated Ash, wt% (ASTM D-874) | 0.96 | 0.96 | 0.87 | 0.87 | 0.88 |
| Quart UPC Code | 0-74804-01308-5 | 0-74804-01309-2 | 0-74804-01310-8 | 0-74804-01311-5 | 0-74804-01312-2 |
| Case UPC Code | 0-74804-15155-8 | 0-74804-14798-8 | 0-74804-14799-5 | 0-74804-14800-8 | 0-74804-15159-6 |
| Case SCC-14 Code | 1-00-74804-05155-8 | 1-00-74804-04798-8 | 1-00-74804-04799-5 | 1-00-74804-04800-8 | 1-00-74804-05159-6 |
| 5 Quart UPC Code | 0-74804-03992-4 | 0-74804-01426-6 | 0-74804-01427-3 | 0-74804-01428-0 | 0-74804-03345-8 |
| Case UPC Code | 0-74804-13992-1 | 0-74804-11426-3 | 0-74804-11427-0 | 074804-11428-7 | 0-74804-13345-5 |
| Case SCC-14 Code | 1-00-74804-03992-1 | 4-00-74804-01426-4 | 4-00-74804-01427-1 | 4-00-74804-01428-8 | 1-00-74804-03345-5 |
| Drum UPC Code | 0-74804-03418-9 | 0-74804-03399-1 | 0-74804-03400-4 | 0-74804-03401-1 | 0-74804-03440-0 |



Distributed by Old World Industries, LLC Northbrook, IL 60062
 p 800.323.5440 www.peakauto.com

©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

RUN TRUE™